

MEMO

GO-DEVIL ENGINE UNDER WATER

NO. 20

DATE: 11/18/03

RE: ALL GO-DEVIL MODELS

Procedure for Go-Devil Engine that has been under water.

*****THIS PROCEDURE SHOULD BE DONE AS SOON AS POSSIBLE AFTER THE ENGINE IS REMOVED FROM THE WATER. FAILURE TO DO THIS IMMEDIATELY CAN RESULT IN DAMAGE TO THE ENGINE DUE TO CORROSION*****

- 1) Remove spark plugs
- 2) Remove air filter and replace
- 3) Drain oil and replace oil
- 4) Drain carburetor and flush fresh fuel through the carburetor.
- 5) Spin engine over for 15-20 seconds to blow water out of cylinders.
- 6) Spray WD40 in cylinders.
- 7) Spin engine over to remove water and WD40 from cylinders.
- 8) Spray spark plugs with WD40 to remove water. Spark plug will not fire if wet with water.
- 9) Install spark plugs.
- 10) Start engine. Use starting fluid if necessary.
- 11) Run engine for 15 minutes.
- 12) Change oil and oil filter.
- 13) Start and run engine for 2 hours to dry out completely.

*****NOTE*****

If engine has been under saltwater, wires and electrical components may be corroded and damaged due to electrolysis from the battery being connected. Replace parts if necessary.

